

Technical Rider 2025

Contact pre-production

Maurits de Vries

Mobile: +31(0) 6 4220 2981

E-mail: mauritsdevries@gmail.com

Band

David Evers - Lead Vocals

Pascal Vugts - Bass guitar + backing vocals Sauro Locchi - Electric guitar + backing vocals

Michiel Oskam - Electric guitar

Maurits de Vries - Drums

Crew

Norbert de Waal - Roady

Charlotte Grips - Photographer



Equipment

Lead vocals (David)

Will bring his own handheld wireless microphone with transmitter:

• Shure BLX2-k14

Electric guitar 1 & backing vocals 1 (Sauro)

- Marshall top + cabinet
- Pedalboard
- Request: Microphone for backing vocals to be provided by venue

Electric guitar 2 (Michiel)

- Marshall Silver Jubilee Head 2555x
- 2x12" Bogner cabinet
- Pedalboard

Bass guitar & backing vocals 2 (Pascal)

- Hartke3500 350W bass-amp (top)
- Hartke 410XL 4x10" (cabinet)
- Boss overdrive pedal
- Request: Microphone for backing vocals to be provided by venue

Drums (Maurits)

- Tama Starclassic drums: 22" kick, 12" rack tom, 14" & 16" floortoms + snare
- Amedia Cymbals: 2 or 3 crashes, hihat, ride, maybe some effect cymbals
- Roland TD2 drum module -*1
- Behringer Xenyx 802S mixer -*2
- Wired in-ear monitors -*3
- Request: Microphone with on/off switch to be provided by venue -*4
- *1: The TD2 drum module is used for samples, backing tracks & clicktrack.

It has 2 mono outputs: left & right.

Mono out LEFT = Clicktrack

Mono out RIGHT = Backing Track & Samples

*2: The TD2 drum module outputs go to the Behringer mixer:

Mono out LEFT (=Clicktrack)

=> only goes to mixer

Mono out RIGHT (=Backing track & samples)


=> goes to FoH and mixer

Request: D.I. provided by venue (to split channels).

- *3: The Behringer mixer is connected to wired in-ear monitors which are only used for the tracks which contain backing tracks & clicktrack. The rest of the monitor mix goes throughout the provided monitor.
- *4: Drummer wants to be able to speak to the crowd and band. Therefore a a microphone with **on/off switch** is requested to prevent audio bleed. This microphone will not be used for singing.



Stageplot



Monitor

Preferably each crüe member gets his own monitor. The monitor mixes will be set on location in consultation with the front of house engineer.



Input list

| # | Instrument | Mic./DI | Stand |
|----------------------------|-----------------|-----------|-----------------|
| 1 | Kick In | Dynamic | N.A. |
| 2 | Kick Out | Dynamic | Clip-on / stand |
| 3 | Snare Top | Dynamic | Clip-on / stand |
| 4 | Snare Bottom | Dynamic | Clip-on / stand |
| 5 | Hi-Hat | Condensor | Clip-on / stand |
| 6 | Rack Tom | Dynamic | Clip-on |
| 7 | Floor Tom | Dynamic | Clip-on |
| 8 | Floor Tom | Dynamic | Clip-on |
| 9 | Overhead L | Condensor | Large Boom |
| 10 | Overhead R | Condensor | Large Boom |
| 11 | Drummodule | DI | N.A. |
| 12 | Bass DI | DI | N.A. |
| 13 | Bass | Condensor | Small Boom |
| 14 | Guitar Amp 1 | Condensor | Small Boom |
| 15 | Guitar Amp 2 | Condensor | Small Boom |
| 16 | Lead vocal | Dynamic * | Straight stand |
| 17 | Backing Vocal 1 | Dynamic | Straight stand |
| 18 | Backing Vocal 2 | Dynamic | Straight stand |
| 19 | Talk mic drums | Dynamic | Large Boom |
| * will be provided by band | | | |

Microphone types and placement to preference of front of house engineer.

Backdrop

A digital image of the Wrecking Crüe logo (name) will be provided. In case a projector is available, the logo can be projected on the wall. Therefore ideally, the background should be solid white or black.

Light / Special FX

As Wrecking Crüe stands for a good time-good vibes only party, all special effects that contribute to a great show and dito experience are welcome. For example: smoke machines, fancy lighting, laser machines or bikini dressed foxy ladies in dance cages.

Merchandise

Not applicable.